

Components

SKU	Description	Package Quantity
GEMM71-W1	Tetra® miniMAX Wet White 7100K	100 ft (30.48 m)/box (250 modules)
GEMM50-W1	Tetra® miniMAX Wet Warm White 5000K	100 ft (30.48 m)/box (250 modules)
GEMM41-W1	Tetra® miniMAX Wet Warm White 4100K	100 ft (30.48 m)/box (250 modules)
GEMM32-W1	Tetra® miniMAX Wet Warm White 3200K	100 ft (30.48 m)/box (250 modules)
GEMM71-2	Tetra® miniMAX White 7100K	100 ft (30.48 m)/box (250 modules)
GEMM50-2	Tetra® miniMAX Warm White 5000K	100 ft (30.48 m)/box (250 modules)
GEMM41-2	Tetra® miniMAX Warm White 4100K	100 ft (30.48 m)/box (250 modules)
GEMM32-2	Tetra® miniMAX Warm White 3200K	100 ft (30.48 m)/box (250 modules)
GEMMRD-1	Tetra® miniMAX Red	100 ft (30.48 m)/box (250 modules)
GEMMBL-1	Tetra® miniMAX Blue	100 ft (30.48 m)/box (250 modules)
GEMMGL-1	Tetra® miniMAX Green	100 ft (30.48 m)/box (250 modules)
GEMMPO-1	Tetra® miniMAX Orange	100 ft (30.48 m)/box (250 modules)
9409	18 AWG Supply Wire (0.82 mm ²)	500 ft./spool (152.4 m)
191600041	22-14 AWG Twist-On Wire Connectors (0.33 - 2.08 mm ²)	500/ PK
192160004	18-14 AWG In-line Connectors (IDC) (0.82-2.08 mm ²)	500/ PK

Technical Specifications

Color	Wavelength	Typical Brightness (lumens/module)	Typical Brightness (lumens/ft.)	Energy Consumption (Strip/Module)	Energy Consumption (System/Module)	Power Supply Loading	Viewing Angle
Tetra miniMAX White Wet	7100K, 5000K	36	90	0.32	0.38	68ft (170 modules)	150
Tetra miniMAX Warm White Wet	4100K, 3200K	34, 30	85, 75	0.32	0.38	68ft (170 modules)	150
Tetra miniMAX White	7100K, 5000K	36	90	0.32	0.38	68ft (170 modules)	150
Tetra miniMAX Warm White	4100K, 3200K	34, 30	85, 75	0.32	0.38	68ft (170 modules)	150
Tetra miniMAX Red	625nm	11	27	0.39	0.47	60ft. (150 modules)	150
Tetra miniMAX Blue	467nm	8	19	0.39	0.47	60ft. (150 modules)	150
Tetra miniMAX Green	530nm	24	60	0.39	0.47	60ft. (150 modules)	150
Tetra miniMAX Orange	606nm	19	48	0.48	0.59	60ft. (150 modules)	150

Specification Item	Specification															
LEDs/ Module	3															
Module/ft.	2.5															
Cutting Resolution	Cut on wire between every module															
Power Supply	GEPS12-20 Input: 90-264VAC; Output: 12VDC GEPS12-60-NA Input: 108-305VAC; Output: 12VDC GEPS12-60-GL Input: 108-305VAC; Output: 12VDC GEPS12W-60 Input: 90-264VAC; Output: 12VDC GEPS12D-60U Input: 90-305VAC; Output: 12VDC															
Maximum Supply Wire Limits	<table border="1"> <thead> <tr> <th>60W, 80W, 100W, 180W</th> <th>20W</th> <th>Supply Wire Gauge</th> </tr> </thead> <tbody> <tr> <td>15 ft. (4.6 m)</td> <td>30 ft. (9.1 m)</td> <td>18AWG/0.82mm² supply wire - 9409</td> </tr> <tr> <td>23 ft. (7.0 m)</td> <td></td> <td>16AWG/1.31mm² supply wire</td> </tr> <tr> <td>38 ft. (11.6 m)</td> <td></td> <td>14AWG/2.08mm² supply wire</td> </tr> <tr> <td>65 ft. (19.8 m)</td> <td></td> <td>12AWG/3.31mm² supply wire</td> </tr> </tbody> </table>	60W, 80W, 100W, 180W	20W	Supply Wire Gauge	15 ft. (4.6 m)	30 ft. (9.1 m)	18AWG/0.82mm ² supply wire - 9409	23 ft. (7.0 m)		16AWG/1.31mm ² supply wire	38 ft. (11.6 m)		14AWG/2.08mm ² supply wire	65 ft. (19.8 m)		12AWG/3.31mm ² supply wire
60W, 80W, 100W, 180W	20W	Supply Wire Gauge														
15 ft. (4.6 m)	30 ft. (9.1 m)	18AWG/0.82mm ² supply wire - 9409														
23 ft. (7.0 m)		16AWG/1.31mm ² supply wire														
38 ft. (11.6 m)		14AWG/2.08mm ² supply wire														
65 ft. (19.8 m)		12AWG/3.31mm ² supply wire														
Operating Environment	-40 °C to +60 °C															
Module Dimensions (h x l x w) Wet	0.31 x 2.27 x 0.72 in (9.5 x 57.7x 18.2 mm)															
Module Dimensions (h x l x w)	0.31 x 1.89 x 0.47 in (8 x 48 x 12 mm)															
Sign Dimensions	For best results, recommended sign depth is 1.5 inches (38mm) or greater															
Warranty	GE offers a limited system warranty of up to five (5) years															
System Certifications	UL Recognized #E219167, UL Classified #E229508, CE, C-tick, RoHS, IP66 rated for dry, damp or wet location															



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2015 GE.

SIGN099 (Rev 01/12/15)

GE
Lighting

Tetra® miniMAX

LED Lighting System

Wet or dry—our **brightest** solution for **small** channel letters



 imagination at work

Tetra® miniMAX

Maximized Output. Minimized Expense.

Tetra® miniMAX—the remarkable LED system designed for small channel letters as shallow as 1.5 inches in depth—is now **10%** brighter than our previous product. It delivers incredibly uniform light, installs easily and operates efficiently. Working closely with sign builders and owners, we've refined our design to improve performance while decreasing the amount of product required, further reducing installation and material costs. Our system can now operate 68 feet of product per 60W power supply (up from 60 feet in our previous design) and deliver **13%** greater loading for even better material and installation labor savings.

10% Brighter!



Powerful OptiLens™

Tetra miniMAX features **OptiLens™** a patented technology that captures otherwise wasted light and redirects it towards the illuminated surface with impressive uniformity. It optimizes each LED—which enables wider stroke spacing—reducing the amount of material needed per sign while helping protect the LED against moisture, humidity, damage and corrosion.

New Tetra® miniMAX Wet Location Rated

Now there's a miniMAX solution for **wet locations** where saturation with water or other liquids is likely. It's all the same performance features of miniMAX—plus overmolded design that protects against water egress, dust and damage and a special module top surface to eliminate water retention—no separate enclosure is required.



a product of
ecomagination™

Can cut product required almost in half

Many LED systems use about 13 LED modules in 2 rows to fill a capitol "T" channel letter that's 2 feet high.

Improved **Tetra miniMAX**, requires just 7 LED modules to fill the exact same letter (giving up some brightness) while providing outstanding uniformity. That's **46% fewer modules**.

Use one row, not two. **Tetra miniMAX** stretches stroke spacing to an impressive 7 inches in a 3-inch depth channel while maintaining impressive light uniformity on the sign face. It protects your customers' brand image while reducing product costs and saving you installation time.

Total GE Reliability

To ensure every **Tetra miniMAX** installation will operate brilliantly for years, we perform the most extensive, stringent testing in the industry. Rather than rely solely on test data from LED suppliers, we test the LED, sub-system and complete system at our in-house and independent laboratories around the world. Validation of our designs, components, products and processes include high-temperature, high-humidity and accelerated life testing.